

## DESCRIPTION

Prembond 16A is a non setting, self supporting mastic which may be applied to wet surfaces and will seal ducts and conduits against ingress of gas and water. It complies with British Telecom Specification M212C. For sealing cable ducts, conduits and service entry pipes or sleeves particularly below ground level to prevent entry of gas or water into buildings. It may also be used for profiling mechanical joints on hot pipes to allow application of tapes.

**COMPOSITION:** Firm mastic based on polybutene, fatty acids, mineral fillers, organic fibres and water displacing materials.

Typical properties	DATA
Colour	Pale Yellow
Specific gravity	1.73
Specific Volume	578 cm <sup>3</sup> /kg
Flash point	Withstands 35kPa (5 lb/in <sup>2</sup> ) air pressure for over 15 minutes. Withstands 20kPa (2 metre head) water pressure for over 60 minutes
Pressure resistance	Adheres to wet or dry surfaces of the following: iron, steel, glazed earthenware, lead, brass, polythene and PVC
Adhesion	0°C to 35°C
Temperature Range	-15°C to 100°C

<b>PACKING</b>	330mm x 40mm x 40mm. 8 x 1kg strips per carton Corrugated Strips 350mm x 60mm 100 x approx 160g strips per carton
----------------	--